

CRACK REPAIR ADHESIVES

Seal Out Water or Restore Strength To Concrete



ETI EPOXY

High strength, rigid crack repair



ETI epoxies are two-component epoxy formulations designed to provide a structural repair of cracks in concrete.

- Available in two viscosities: ETI-LV (*low viscosity*) and ETI-GV (*gel viscosity*) for a wide range of crack widths
- Packaged in 22 ounce cartridges, that are ideal for medium to large projects
- A rigid repair that seals the crack from moisture
- Suitable for pressure injection or gravity feed
- Cracks can be dry or wet (*but can have no actively leaking water*)
- Suitable for contact with potable water (*per NSF/ANSI Standard 61*) (ETI-LV)
- Meets the requirements of ASTM C-881 Type I, II, IV and V, Grade 1 (ETI-LV), or Grade 3 (ETI-GV), Classes B&C

Product Information

Model	Cartridge Capacity ounces (cubic inches)	Viscosity	Suitable Crack Width (in)	Mixing Nozzle	Carton Quantity
ETILV22	22	1790 cps	1/64 - 1/4	EMNO22	10
ETIGV22	(39.7)	Gel	3/32 - 1/4	(included)	

CRACK-PAC® EPOXY

High strength, rigid crack repair that dispenses from a standard caulking tool



Crack-Pac is a two-component, low-viscosity epoxy that provides a high strength repair for cracks in concrete.

- Single cartridge system which easily dispenses from a standard caulking tool
 - A rigid repair that seals the crack
 - Suitable for pressure injection or gravity feed
 - Cracks can be dry or wet (*but can have no actively leaking water*)
 - Meets the requirements of ASTM C-881 Type I & II, Grade 1, Classes B&C
- Crack-Pac is also available in a Crack-Pac Kit which contains all of the material needed to inject 8 lineal feet of crack (*model ETIPAC10KT*).

Product Information

Model	Cartridge Capacity ounces (cubic inches)	Viscosity	Suitable Crack Width (in)	Carton Quantity
ETIPAC10	9 (16.2)	1400 cps	1/64 - 1/4	12
ETIPAC10KT	18 (32.4)			2 Kits

CRACK-PAC® FLEX-H₂O™ POLYURETHANE

Water activated, flexible crack sealer



Crack-Pac Flex-H₂O is a single component polyurethane that seals dry, wet and actively leaking cracks.

- Seals seeping or mildly leaking cracks
- 400% elongation allows for crack movement
- Can be dispensed with a standard caulking tool
- Expands to fill voids and close off the back of the crack (*suitable for some masonry applications*)
- Fast reacting – reaction begins in under 1 minute; expansion completed within 3 minutes
- Non-shrinking hydrophobic formula with the elongation and flexibility of a hydrophilic resin
- 20:1 expansion ratio (*unrestricted rise*) means less material needed
- Also suitable for dry cracks (*with water added*)

Crack-Pac Flex-H₂O is also available in a kit which contains all of the material needed to inject 8 lineal feet of crack (*model CPFH09KT*).

Product Information

Model	Cartridge Capacity ounces (cubic inches)	Viscosity	Suitable Crack Width (in)	Carton Quantity
CPFH09	9 (16.2)	600 cps	1/32 - 1/4	12
CPFH09KT	18 (32.4)			2 Kits



800-999-5099
www.simpsonanchors.com

© 2008 Simpson Strong-Tie Company Inc.
Printed in the U.S.A.

F-SAS-CRKREP08 5/08 exp. 6/10

CRACK REPAIR ADHESIVES

SIMPSON

Strong-Tie
ANCHOR SYSTEMS



Crack Repair Adhesive Suitability Matrix

Application/Feature	ETI Epoxies	Crack-Pac	Crack-Pac Flex-H ₂ O
Seals the crack against moisture	✓	✓	✓
Restores strength to the concrete	✓	✓	—
Expands to fill voids	—	—	✓
Flexible (<i>allows crack movement</i>)	—	—	✓
Suitable to seal cracks in masonry	—	—	✓
Suitable to dry and wet cracks	✓	✓	✓
Suitable for cracks actively leaking water	—	—	✓
Suitable installation procedure(s)	Pressure injection or gravity feed	Pressure injection or gravity feed	Pressure injection
Dispensing tool	Manual: EDT22B Battery: EDT22CKT Pneumatic: EDT22AP	CDT10 or standard caulking tool	CDT10 or standard caulking tool

This table contains general recommendations regarding product suitability. Suitability for any specific project should be determined by a qualified professional.

CRACK INJECTION ACCESSORIES

- E-Z-Click injection ports and fittings
- Manual, battery and pneumatic dispensing tools for 22 oz. cartridges
- Paste-over epoxies: CIP, ET, ETR and SET



Simpson Strong-Tie tools and ports speed up production on the job



E-Z-Click injection ports and fittings



Paste-over epoxies



For complete technical information on crack repair adhesives, please see the current Simpson Strong-Tie Anchoring and Fastening Systems for Concrete and Masonry catalog or visit www.simpsonanchors.com.

This flier is effective until June 30, 2010 and reflects information available as of May 1, 2008. This information is updated periodically and should not be relied upon after June 30, 2010; contact Simpson Strong-Tie for limited warranty and current product information.

SIMPSON

Strong-Tie
ANCHOR SYSTEMS

IN THE SPECS - ON THE JOB - AT YOUR SERVICE™

Simpson Strong-Tie offers a full line of anchors, adhesives, P.A.T. and drill bits for all of your anchoring and fastening applications. Visit our website or request our catalog for complete information.

Home Office

5956 W. Las Positas Blvd.
Pleasanton, CA 94588
FAX: 925/847-1603

Southwest U.S.A.

260 N. Palm Street
Brea, CA 92821
FAX: 714/871-9167

Southeast U.S.A.

2221 Country Lane
McKinney, TX 75069
FAX: 972/542-5379

Western Canada

11476 Kingston St.
Maple Ridge, BC V2X 0Y5
FAX: 604/465-0297

Northwest U.S.A.

5151 S. Airport Way
Stockton, CA 95206
FAX: 209/234-3868

Northeast U.S.A.

2600 International Street
Columbus, OH 43228
FAX: 614/876-0636

Eastern Canada

5 Kenview Blvd.
Brampton, ON L6T 5G5
FAX: 905/458-7274

Warehouses & Manufacturing:

Eagan, MN; Enfield, CT; Gallatin, TN;
High Point, NC; Jacksonville, FL; Jessup, MD;
Kent, WA; Langley, BC; Ontario, CA

800-999-5099

www.simpsonanchors.com

© 2008 Simpson Strong-Tie Company Inc.

Printed in the U.S.A.

F-SAS-CRREP08 5/08 exp.6/10